

PAPER NAME

1833-6935-2-PB.pdf

WORD COUNT	CHARACTER COUNT
6431 Words	35863 Characters
PAGE COUNT	FILE SIZE
13 Pages	488.1KB
SUBMISSION DATE	REPORT DATE
Jan 26, 2024 9:31 AM GMT+7	Jan 26, 2024 9:31 AM GMT+7

• 8% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

• 8% Submitted Works database

• Excluded from Similarity Report

- Internet database
- Crossref database
- Bibliographic material

- Publications database
- Crossref Posted Content database
- Cited material



Preventive Maintenance Analysis Based on Mean Time Between Failure (MTBF) and Mean Time to Repair (MTTR)

Silva 22 Alfionita¹, Fakhri Ikhwanul Alifin² ¹ Undergraduate Program, Department of Industrial Engineering, Universitas Singaperbangsa Karawang, Karawang, Jawa Barat

²Department of Industrial Engineering, Universitas Singaperbangsa Karawang, Karawang, Jawa Barat

Article Info

Article history:

Received September 2, 2023 Accepted September 22, 2023 Published November 6, 2023

Keywords:

Preventive Maintenance Mean Time Between Failure (MTBF) Mean Time to Repair (MTTR) Failure Mode Effects Analysis (FMEA)

ABSTRACT

A manufacturing company's ability to meet its goals depends heavily on the smooth operation of its production process. Hence, it is crucial to have optimal maintenance to run the business smoothly. This study aims to identify the root cause of the malfunction in the soda and dolomite bucket elevators by analyzing the MTBF, MTTR, and a qualitative assessment through Failure Modes and Effects Analysis (FMEA). The study also found that actual preventive maintenance (PM) action was usually 3 days ahead of the scheduled PM (i.e., 30-day cycle). This issue indicates that the company may experience unexpected failures and other problems associated with the PM action. The FMEA results revealed that suboptimal maintenance by company staff and other root causes potentially affect the PM enactments indicated by the high Risk Priority Number (RPN) score. Finally, several recommendations are proposed to cope with the issues according to the findings of this study.



Corresponding Author:

Silvana Alfionita,

epartment of Industrial Engineering,

niversitas Singaperbangsa Karawang,

Jl. HS. Ronggowaluyo, Telukjambe Timur, Karawang, Jawa Barat. *Email*: silvanaalfionita@gmail.com

INTRODUCTION 1.

Regular maintenance is essential for repairing damages and improving machine performance. This is especially important in industries that require high-quality output and constantly evolving production processes. A malfunctioning machine can cause production processes to come to a standstill. Therefore, maintenance on machines before any damage occurs is crucial in reducing repair costs and maintaining product quality [1]. Vernor's opinion [2] In his book Maintenance Planning and Control Handbook, Maintenance is defined as a combination of all technical, administrative, and managerial actions throughout the life cycle of an item, aimed at maintaining or restoring it to a condition where it can fulfill its designated function. Maintenance is a crucial set of care and repair activities that ensure the consistent reliability and availability of machines or production equipment. This enables them to produce high-quality products efficiently and cosseffectively and hence, increase customers' satisfaction by protecting them from nonconformity product. Model failure process of each type of components, which considers a bidirectional (or mutual) failure interaction between the C and NC components. Hence, each component has two types of failures -i.e., natural failure and induced failure [3][4]. As Sudarno [5] explains, this process is essential to the success of any production operation. Maintenance in the Industry 4.0 environment is essential for enhancing maintenance operation capabilities and achieving optimal efficiency [6]. It is crucial to understand that maintenance can be classified into two types: Preventive and Corrective. Preventive Maintenance is a proactive approach that aims to prevent unexpected downtime. It significantly prolongs equipment lifespan, enhances performance and efficiency, and ultimately reduces overall maintenance expenses. It is imperative to prioritize Preventive Maintenance to ensure minimal disruptions and keep your equipment running smoothly [7]. Preventive Maintenance is conducted by performing scheduled maintenance on equipment, such as cleaning, lubrication, replacement of worn components, and equipment adjustments [8]. Preventive maintenance keeps equipment in excellent condition to prevent downtime or damage. It's done based on time

intervals or usage [9]. Maintaining optimal equipment and system conditions is crucial to avoiding substantial damage and downtime [9]. Corrective Maintenance is the essential process of restoring equipment to its normal functioning state after experiencing any kind of failure or damage [10]. Corrective maintenance (CM) needs to be implemented on a machine that has experienced failure to restore its operational functionality [11]. Understanding the management of machine performance maintenance is crucial, and it comprises three vital components: Reliability, Maintainability, and overall machine Availability. These components are measured by Mean Time Between Failure (MTBF), Mean Time to Repair (MTTR), and Availability-focused maintenance, respectively. Conducting Availability-focused maintenance is imperative in determining the capability of physical assets to perform as intended [12].

PT. MI Maintenance plays a crucial role in achieving the Quality Objective target (Zero Breakdown) within the Engineering Department to support the production target of 91% efficiency. Reliability is the probability of an item performing a predetermined function under specific operational and environmental conditions for a specified period [13]. Based on the company's trouble report data, it is indicated that there are three pieces of equipment with the highest damage frequency. These are the soda and dolomite bucket elevator equipment with a damage frequency of 37%, the 16 x 5 feet power screen equipment with a damage frequency of 33%, and the silica sand bucket elevator equipment 1032 due to its highest damage count in 2022. Furthermore, field observations reveal that the maintenance cost for this equipment has been consistently increasing from 2019 to 2022. This research will discuss the Bucket Elevator Soda & Dolomite 1032 equipment as it had the highest damage rate in 2022. Furthermore, the maintenance cost of this equipment has been consistently increasing from 2019 to 2022. To address this issue, we need to identify the root cause of the problem and find its solution asing the Mean Time Between Failure (MTBF) and Mean Time to Repair (MTTR) calculation methods. The purpose of this investigation is to pinpoint the underlying factors that computed to the malfunction of the soda and dolomite bucket elevator. This will be accomplished by examining the Mean Time Between Failure (MTBF) and Mean Time to Repair (MTTR), as well as performing a qualitative assessment through the Failure Mode Effects Analysis (FMEA) method.

According to Prabhakar, al [14] MTBF is a measurement of the average time between failures in a system or component. This can be calculated by dividing the Sum operation time by the number of failures. Meanwhile, Mean Time to Repair measures the average time it takes to repair a system or component after a failure. MTTR can be calculated by dividing the Sum of downtime by the number of recovery or repair events [15]. FMEA (Failure Mode and Effects Analysis) is a systematic method for identifying, analyzing, and reducing the risk of failure in a process, product, or system. This method involves identifying potential failures, assessing severity, probability of occurrence, and failure detection capabilities. The goal is to identify preventive or corrective at a can reduce the risk of failure and improve the quality and reliability of the product or process [16]. A clisk Priority Number (RPN) is a number used in FMEA to measure the level of risk of failure. RPN is obtained by multiplying three critical factors in FMEA analysis, namely Severity (severity of failure impact), Occurrence (frequency of failure), and Detection (ability to detect failures before reaching customers). The higher the RPN value, the higher the level of risk associated with such failures [17].

The previous research conducted by Maciej Kuboń, et al [18] Indicates that the parameters of MTBF (Mean Time Between Failures) and MTTR (Mean Time to Repair) have a significant influence on the reliability and productivity of technical systems. A higher MTBF value, indicating longer periods between failures, leads to increased system reliability and productivity. Conversely, a shorter MTTR value, indicating faster repair times, also contributes to improved system performance. Based on the findings of previous research Oki Sunardi, et al [19] discuss the effectiveness of machines in the manufacturing industry and emphasize the importance of maintenance in improving productivity and reducing costs. The study uses the Total Productive Maintenance approach and calculates the Mean Time Between Failure and Mean Time to Repair. The findings suggest implementing preventive maintenance and improvements to increase machine life. The findings of previous research Indicate that the critical components of the 1000-ton hydraulic press machine are the V-Packing and Contactor. V-Packing experiences 8 failures at a rate of 32% of the total failures, while the Contactor experiences 6 failures, accounting for 24% of the total failures. Overall, this study provides a step-by-step approach to determine the optimal maintenance actions for the 1000-ton hydraulic press machine based on the RCM method. Critical components are identified, and reliability analysis is conducted to calculate the values of MTBF (Mean Time Between Failures) and MTTR (Mean Time to Repair) [20]. The findings of previous research the study analyze the current maintenance management condition and propose a change in the maintenance schedule based on the Mean Time Between Failure (MTBF) and Mean Time to Repair (MTTR) methods. The research found that the maintenance schedule for the centrifugal compressor machines should be changed from every 3 months to every 2 months [21]. A previous study examined performance maintenance

by analyzing ²Mean Time Between Failure (MTBF), Mean Time To Repair (MTTR), and machine availability data from May 2019 to April 2020. The study aimed to assess the maintenance system's condition and determine areas for improvement. The results showed that the machine's reliability is unstable, the MTTR graph is stable, indicating good maintenance operator skills, and machine availability needs improvement [22]. The study also calculated the machine's effectiveness using MTBF and MTTR and illustrated machine repair activities using Maintenance Value Stream Mapping (MVSM). Based on the findings, the machine that frequently experiences breakdown is TM-10, mainly due to faulty parts, accounting for 49%. The repair efficiency value increased from 27.93% to 41.67% after repair [23]. Previous research findings [22] showed that there were two critical components with an indication of the increasing failure rate, during wear-out (β value> 1), which are namely cylinder press and EPV with an MTBF value of 89 days for cylinder presses and 231 days for EPV. The results of this study propose updating the curing machine PM schedule [24]. Based on the observational data, the MTBF has reached 3458 minutes, and the MTTR has reached \hat{A} minutes. Meanwhile, the Availability Performance (AP) only reaches 95.1%, which hampers the Extruder type 150's optimal operation and disrupts the production process [25]. The study also calculated the MTBF and MTTR values of each machine and determined the maintenance item's significance by the MTBF value. After analyzing the root causes of the issues, several improvements have been made, demonstrating an increase in the maintenance period for the corrugator, flexo, and glue machines [26]. The study also performed quantitative analysis by calculating MTBF, MTTR, and determining reliability and failure rate. The results showed that the mill fan has the lowest reliability rate based on its Inherent Availability, standing at 79.92% [27]. The machine used must be guaranteed to operate at high performance, so periodic inspections must be carried out. In machine maintenance activities at PT. SNP is not based on damaged data as a reference, and in its implementation is still not programmed. In this study, a solution will be sought to overcome the problem of optimal machine scheduling by considering the cost of repairs and the number of repairmen. The historical data of engine failure will be used to calculate the Mean Time Between Failure (MTBF) and Mean Time to Repair (MTTR) and model the engine maintenance so that it is expected to be able to reduce repair costs [28]. In previous research exciting results were obtained for Mean Time to Repair (MTTR) as follows: sand filter 0.48 hours, bag filter 0.68 hours, cartridge filter 1.22 hours. The Mean Time to Failure (MTTF) values were: sand filter 684 hours, bag filter 190.3 hours, cartridge filter 236.8 hours. Furthermore, the Mean Time Between Failure (MTBF) values were as follows: sand filter averaged 708 hours, bag filter averaged 214.8 hours, and cartridge filter averaged 260.8 hours per year. In addition to MTTR, MTTF, and Mean Time Between Failure (MTBF), other research findings include the reliability values for the filters: sand filter with a value of 0.178, bag filter with a value of 0.0053, and cartridge filter with a value of 0.00889 [29]. The recommendation for PT. XYZ is to implement the autonomous pillar and scheduled part replacement to solve issues at the factory, and to focus on critical work areas; i.e., dryer-cooler station, areas with the highest breakdown duration and mean time to repair (MTTR), and the lowest mean time between failures (MTBF) [30]. The analysis of the Dump Truck HD 1500-7 unit's maintenance performed from February to April 2022 revealed that the average MTBF value is 352.9 hours, the average MTTR value is 5.388 hours, and the average PA value is 96.38% [31].

However, the research that combines the quantitative and qualitative approaches to analyze the actual predictive maintenance is still scarce. According to the above-mentioned research, prior studies utilized only either qualitative or quantitative approaches. Thus, in this research, a new approach to analyzing and identifying root causes is conducted from a managerial perspective by integrating quantitative approaches (i.e., MTBF and MTTR) with qualitative methods such as fishbone diagrams and a ailure Mode and Effects Analysis (FMEA). In this study, a fishbone diagram is utilized to analyze potential root causes. Whilst, FMEA is generated to identify potential failures through the Risk Priority Number (RPN) ob gined by this method, which allows the company to apply some preventive actions or improvements to reduce the risk of failure and enhance the quality and reliability of products or processes.

The following is the structure of this study. In the first section, the background and literature review have been explained by this study. Moreover, the second section will describe the research method used in this study study is a combination of quantitative (i.e., MTBF and MTTR) and qualitative descriptive (i.e., fishbone and FMEA) approach, which is assumed to be more comprehensive than the prior studies. Next, the third section will elucidate the findings and analysis, leading to the solutions derived from this research, and the final section will comprise the conclusion and suggestion.

2. SESEARCH METHOD

The research methodology used in this study is a combination of quantitative (i.e., MTBF and MTTR) and qualitative descriptive (i.e., fishbone and FMEA) approach, which is assumed to be more comprehensive than the prior studies. These approaches enables researchers to delve deeper and provide a comprehensive overview of the various aspects related to machine maintenance in the PT. MI during 2022. The data utilized in this study comprises secondary and primary data. Secondary data, which serves as the initial foundation of

the study, are obtained from daily maintenance reports and data recorded in the company's systems. Daily maintenance reports provide insight into various issues that arise during day-to-day operations. Data from the company's systems includes valuable historical records related to machine maintenance. Through the analysis of this secondary data, researchers can understand standard patterns and trends that may emerge in machine failures and track how maintenance management has evolved so far. However, this secondary data is only a starting point.

To gain a deeper and contextual understanding primary data collection is carried out, researchers conducted interviews with key stakeholders, including 1 Superintendent, 1 Supervisor, and 3 Mechanical Staff from PT. MI. This interview opens the door to gaining valuable insight into their experience in dealing with machine maintenance issues, existing policies and procedures, and any obstacles that may be encountered in the engine repair process. The data collected from these interviews includes essential information such as the most common types of machine breakdowns and factors causing engine failure. In addition, respondents also provided their perspectives on the lead times involved in the repair process and the associated maintenance costs.



Figure 1. Research process flow



After the required data has been gathered, the next step is to process the data according to the established method based on the characteristics of the problem. The aim is to categorize the damage data throughout the yet 2022 to identify the equipment that most frequently experiences malfunctions. Subsequently, calculations of Mean Time Between Failure (MTBF) and Mean Time to Repair (MTTR) are conducted as essential parameters for analyzing equipment performance. Next, an analysis is proceed on the results of the MTBF and MTTR calculations. The next step involves qualitative evaluation asing the Failure Mode and Effects Analysis (FMEA) method as a basis for formulating solutions to the identified issues. Following that, conclusions are drawn, and recommendations are provided based on the results of the analysis and discussion that have been conducted.

Furthermore, data from both sources will be analyzed together to identify patterns, challenges, and potential improvements in machine maintenance management at PT. MI. The findings of this study will provide a comprehensive picture of machine maintenance issues during 2022 and may form the basis for better recommendations for future machine maintenance management.

3. RESULTS AND ANALYSIS

After data collection was carried out, three machines with the highest amount of damage were obtained as follows:

No	Problem Type (Machine)	Frequency	%	Cumulative (%)
1	Preventive Bucket Elevator Soda and Dolomite 1032	11	37%	37%
2	Preventive power screen 16 x 5 feet	10	33%	70%
3	Preventive bucket elevator silica sand 1031	9	30%	100%
	Sum	30	100%	

Table 1. Highest Damage Frequency Data

Furthermore, the calculation of MTTR and MTBF is carried out with the following equation.

MTRE	_	Total (Downtime-Up Time)	(1)
MIDF -	_	Number of Failure	(1)
MTTR	=	Total Maintenance Time	(2)
I II		Number of Repair	(2)

MTTR is calculated from the length of repair time while *MTBF* is calculated from the last range of the engine repaired until the machine is damaged again.

Table 2. MITIK and MIBF Calculation Results							
Equipment	Description	Action	Rep	MTTD	MTDE		
code	Description	Acuon	Start	Finish	WIIK	WIIDI [,]	
	Found the Condition of the Bolt Bucket Has Begun to Break Down	Replace Bolt &; Nut Bucket elevator + Ring (30 Sets)	21/01/2022 09:30	21/01/2022 10:30	60'	70770'	
100021151	Bowl Condition &; Bucket Bolts Damaged (Wear & Dent)	Replace 400or225 Bucket Bowl (5pc) + Change Bolt &; Nut Bucket elevator + Ring (30 Sets)	11/03/2022 14:00	11/03/2022 16:00	120'	73620'	

Table 2. MTTR and MTBF Calculation Results

Equipment	D : /:	A - 4 ²	Rep	pair	MTTD	MTBF	
code	Description	Acnon	Start	Finish	MIIK		
	Sensor or Blocked Bucket, Does Not Work Optimally (At the time of the stop, the motor is still operational so that the V. Belt slips and breaks	Replace V. Belt Drive Spare New V. Belt Spa-2432 Rubber (4pc)	01/05/2022 19:00	02/05/2022 21:00	120'	8520'	
	Sensor or Blocked bucket, does not work optimally (at the time of the stop, the motor is still operational so that the V. Belt slips and breaks	Replace V. Belt Drive Spare New V. Belt Spa-2432 Rubber (4pc)	08/05/2022 19:00	08/05/2022 21:00	120'	67260'	
	When P or S work was found, a condition was found that there was a material in the bucket casing	Casing Patch with Glue Silicone (Building & Glazing) (2 Tubs)	24/06/2022 14:00	25/06/2022 15:00	60'	27240'	
	When P or S Work Requires Material Replacement	Replace bucket bowl 400or225 (15pc) &; replace bolt and nut bucket elevator + ring (60 sets) & adjuster elevator belt	14/07/2022 13:00	15/07/2022 15:00	120'	38820'	
	When P or C Work Found &; Bucket Case Damper Condition There Is Material Leakage	Repair Leaks in Damper Casing Bucket, Glue Silicone (Building &; Glazing) (2 Tube), Repair Motor Exs. Diwor S for spare bearings 6210 ZZ C3 (1 pc), bearing 6211 ZZ c3 (1 pc), and motor settings	11/08/2022 14:00	12/08/2022 15:00	60,	50340'	
	When P or C Work Required Regreasing Bearings	Greasing With Car Grease Xhp 222 (0.100 Pie), Damper Lid Bucket Case with Glue Silicone (Building &;	16/09/2022 14:00	17/09/2022 15:00	60,	38820'	

ISSN : 2085-9503 (Print), 2581-1355 (On Line)

Equipment	D : /:	A	Repair		MATD	MTDE	
code	Description	Acnon	Start	Finish	MIIK	MIBF	
		Glazing) (2 Tubs)					
	When P or C work is found, the condition of the bucket is already an indication of damage	Replace 4pc Spare Exs Bucket Bowl. Repair Ws, Replace Bolt &; Nut Bucket elevator Ring (30 sets), and Glue Silicon (Building &; Glazing) (2 Tubs)	14/10/2022 14:00	15/10/2022 15:00	60'	48900'	
	When P or S Work Requires Material Replacement	Replace Bolt &; Nut Bucket elevator + Ring (30 Sets), Replace Bucket Bowl 4 Pc Spare Exs. Repair	18/11/2022 14:00	18/11/2022 15:00	60'	47460'	
	When P or C Work Found &; Bucket Case Damper Condition There Is Material Leakage	Repair Damper Casing Bucket Glue Silicone (Building&Gl azing) (2 Tubs)	21/12/2022 14:00	12/12/2022 15:00	60'		
Sum			900'	471750'			
		Average			81,82'	47175'	
			1 Day = 1440 M	linutes		32,76 Days	
			32,76 <i>Days</i> ≈	33 Days			

Over an entire year, a machine can operate continuously for 24 hours a day. This amounts to a Sum of 525,600 minutes of operational time. By using this Sum of Operation Time, the machine's Availability can be accurately calculated.

 $\begin{aligned} Availability &= \frac{Operating \ Time}{Sum \ Operating \ Time} \times 100\% \\ Availability &= \frac{471750-0}{525600} x \ 100\% = 89,75\% \approx 90\%. \end{aligned}$

(3)

Based on availability calculations, the soda and dolomite 1032 elevator bucket equipment perform optimally with an availability rate of 89.75%, which is just slightly under the optimal standard of 90%. However, it poses a significant risk of damage without proper treatment. Therefore, it is imperative to schedule optimal maintenance to prevent frequent machine damage.

Based on MTBF and MTTR calculations, the actual preventive maintenance (PM) schedule for the Soda and Dolomite 1032 elevator bucket is every 33 days in a cycle. Whilst, the company's required PM schedule is conducted every 30 days. According to these data, the PM actions are often 3 days ahead of the required schedule in overall. This issue will produce sudden failure in the machine which leads to the corrective maintenance (CM) action and hence, produce a higher maintenance costs. Therefore, the company must implement an opportunity maintenance policy to make immediate corrective repairs to damaged parts found in preventive maintenance. This indication demands further investigation through failure rate analysis and the expected number of failures based on damage data obtained at PT. PT. MI.



Chart Maintenance Cost

The chart in Figure 4.1 illustrates a notable rise in maintenance expenses over a while, which may be indicative of inadequate maintenance policies. Our forthcoming research endeavors to delve deeper into this matter by utilizing mathematical modeling and optimizing the model for better outcomes. Currently, we are conducting a thorough analysis to identify the underlying cause of the problem from a qualitative managerial perspective. To facilitate the analysis, we have created a fishbone diagram to explore various potential causes, and we are

also utilizing ailure Mode and Effects Analysis (FMEA) tables. The Fishbone Analysis in this study is based on the MIL-STD 882 standard. MIL-STD 882 is a standard used for system safety engineeing and risk management within the military and defense sectors. It provides guidelines and procedures for identifying, assessing, and mitigating risks associated with potential hazards and failures. The utilization of MIL-STD 882 as the basis for the Fishbone Analysis ensures a structured and comprehensive approach to identifying and analyzing various factors that contribute to the identified problem, aligning with established safety and risk management practices within the defense domain.



Figure 3. Chart Fishbone Problem Equipment bucket elevator soda and dolomite

Furthermore, ² ailure Mode and Effects malysis (FMEA) will be conducted to identify and implement preventive or corrective actions to reduce the risk of failure and enhance the quality and reliability of the product according to the managerial perspectives. The risk emerged that potentially causes the failure are

reprented by Risk Priority Number (RPN). This term is a numerical value used in FMEA to measure the level of risk associated with a failure. The formula for the Risk Priority Number (RPN) are as follows [17]:

RPN = *Occurrence* × *Detection* × *Severity*

(4)

Description:	
Severity	: The score for the failure impact severity
Occurrence	: The score for the frequency of failure occurrence
Detection	: The score for the ability to detect failures before reaching the customer.

Table 3. Tabel Risk Priority Number								
PN	Risk Acceptability	Action						
1-14	Low	Although the risk is low, mitigation still needs to be carried out.						
15-29	Tolerable	If there is a redesign in the future, it is necessary to pay attention to this point to enhance the product's reliability.						
30-49	Undesirable	The risk can still be accepted if it cannot be further mitigated by the organization or technology.						
C.	Intolerable	The risk must be eliminated or reduced through protective measures.						

The higher the RPN value, the greater the level of risk associated with the failure. Here are the weights of each of the three factors.

1. Occurrence

The occurrence is the likelihood that a cause will happen and that it will lead to detrimental consequences from the associated danger.

Table 4. Score Occurrence							
Occurrence							
Category	Score						
Certain to fail (1 failure per hour)	5						
High number (1 failure per day)	4						
Occasional (1 failure per week)	3						
Few (1 failure per month)	2						
Unlikely (1 failure per year)	1						

2. Detection

Detection is the probability that controls (design, processes, inspections, warnings, or alarms) will eliminate, reduce, or capture defects or failures.

Table 5. Score Detection						
Detection						
Category	Score					
Undetectable	5					
Poor	4					
Moderate	3					
Good	2					
Excellent	1					

3. Severity

Severity is a measure of the potential consequences and seriousness of a hazard.

Table 6. Score Severity

Severity						
Category Score						
atastrophic	5					
Critical	4					
Serious	3					
Minor	2					
Negligible	1					

The following are the results of FMEA (Failure Mode and Effects Analysis) and the highest RPN (Risk Priority Number) calculation, which is undesirable. The scoring are conducted according to the expert judgement consisting of 1 Superintendent, 1 Supervisor, and 3 Mechanical Staff.

Table 7. RPN and FMEA Calculation Results

	Failure	Failure	Failure Effect						
NO	Cause	Classification	Component	System	0	D	S	RPN	Solution
1	Damage to engine components such as bearings or shafts	Design	~	~	2,8	3,2	4,8	43	Perform regular lubrication and use lubricants recommended by the manufacturer to maintain optimal engine performance. Perform regular cleaning around bearings and shafts to maintain cleanliness and prevent dirt accumulation. If you observe an increase in temperature or unusual vibration, check further immediately to avoid more serious damage.
2	Improper use or exceeding the load	Misuse	~	~	3,4	3	3,4	34,68	Install temperature and vibration sensors on bucket elevator machines to monitor operational conditions. Conduct regular monitoring and evaluation to ensure that the use of bucket elevator machines is by established standards. Improper use can result in damage to engine components and reduce their service life.
3	The lack of care and cleaning.	Mishandling	~	~	2,2	4,2	3,8	35,11	Perform routine visual inspections to identify signs of damage, dirt, or material buildup that may impede the performance of the bucket elevator machine. Take note of any indications of wear, leaks, or damage to machine components. Record all maintenance and cleaning activities carried out on the bucket elevator machine. Do not forget to document any findings or issues that arise during the inspection for appropriate corrective actions. Utilize a monitoring system to oversee the machine's performance in real time.
4	The staff is not providing optimal care.	Mishandling	~	~	3,4	4,2	3,4	48,55	Optimize staff monitoring while they are performing their tasks, and this can be achieved by utilizing RFID (Radio- Frequency Identification) technology.

Based on the results of the FMEA (Failure Mode and Effects Analysis) table and RPN (Risk Priority Number) calculations, failure causes of staff who perform maintenance are not optimal is the main cause of an increase in maintenance costs on soda and dolomite 1032 elevator bucket equipment during 2019 to 2022. So, the author has two solutions for companies as follows:

- 1. The company needs to monitor the activities of staff who carry out periodic checks on the company's machines, this is based on the results of making and calculating FMEA and RPN tables.
- 2. Based on a bar chart illustrating the increase in maintenance costs from year to year. PT. MI needs to review and improve the company's maintenance policy in the future. One approach is to create mathematical models to predict damage and maintenance costs. The model can then be opmtimized analytically or use a heuristic approach to achieve the best optimal results globally. The second solution will be the focus of subsequent research.

The following is a picture of the RFID (Radio-Frequency Identification) technology scheme for monitoring staff who carry out machine maintenance that has been made by the author:



Figure 4. RFID (Radio-Frequency Identification) Scheme

The following is a description of the RFID (Radio-Frequency Identification) technology scheme for monitoring Staff who perform maintenance on bucket elevator equipment machines in a factory: RFID (Radio Frequency Identification) is used to monitor maintenance on bucket elevator equipment. Each staff member is assigned a unique RFID tag attached to their identity. RFID readers are installed near the equipment area and connected to the monitoring system. The monitoring system records the time and identity of the staff performing the maintenance. This data can be used for analysis, such as tracking maintenance time and staff productivity. Integration with care management systems (CMMS) enables structured reporting and efficient care scheduling. Using this scheme, companies can automatically monitor and record maintenance activities carried out by staff on bucket elevator equipment using RFID technology. This helps improve operational efficiency, ensures timely maintenance, and facilitates monitoring and reporting related to staff performing maintenance on bucket elevator equipment.

4. CONCLUSION

Conclusion

- 1. The calculation results of MTBF and MTTR show that the optimal preventive maintenance schedule is 1 time in 33 days, with a difference of 3 days longer than the actual schedule. Early preventive repairs indicate damage that the company did not predict.
- 2. The soda and dolomite 1032 bucket elevator equipment experienced the most problems during 2022, with the cause of failure identified through FMEA analysis and RPN figures. It is necessary to monitor the activities of Maintenance Staff and review the company's maintenance policy.
- 3. The actual schedule of Preventive Maintenance is quite optimal schedule of Preventive Maintenance, but there is an increase in maintenance costs from 2019 to 2022 that needs to be analyzed.
- 4. This research will be the basis for future research on maintenance system optimization to minimize maintenance costs based on optimal Preventive Maintenance time.

Suggestion

- 1. Companies can further optimize worker monitoring by considering the use of RFID (Radio-Frequency Identification) technology as described in this study.
- 2. Companies in determining scheduling can race on maintenance policies and multiply literature references between the world of education and the industrial world, for example on theories obtained during lectures, and see continuity with real practice in the field.
- 3. Companies should upgrade the database system containing important documents or information so that it is neatly arranged and easy to find when needed.
- 4. Companies can consider optimal preventive maintenance schedules to prevent sudden failures and overcome increased maintenance costs.

REFERENCE

- T. L. A. F. D. A. W. Sri Susilawati Islam, "Analisis Preventive Maintenance Pada Mesin Produksi dengan Metode Fuzzy FMEA," *Jurnal Teknologi Terpadu Vol. 8 No. 1*, pp. 13-20, 2020.
- [2] F. J. Vernor, Maintenance planning and control handbook, New York: McGraw Hill Education, 2001.
- [3] F. I. A. Bermawi P. Iskandar, "Warranty Cost Models for Products Protected by Lemon Laws Considering Mutual Failure Interaction.," 2022 13th International Conference on Reliability, Maintainability, and Safety (ICRMS), pp. 1-6, 2022.

- [4] A. C. B. P. I. Fakhri I. Alifin, "Cost Analysis for Warranted Products Protected by Lemon Laws Considering Failure Interaction," in 6th Asia Pasific Conference on Manufacturing Systems and 4th International Manufacturing Engineering Conference (APCOMS-IMEC 2022), Indonesia, 2022.
- [5] Sudarno, "Manajemen Pemeliharaan Mesin Produksi," Jurnal Teknik Mesin, 5(2), pp. 131-138, 2015.
- [6] D. A. G. M. Alexandros Bousdekis, "Predictive Maintenance in the 4th Industrial Revolution: Benefits, Business Opportunities, and Managerial Implications," *IEEE Engineering Management Review*, pp. 57-62, 2020.
- [7] B. D. A. R. Mohamad Syaripudin, "Usulan Perawatan Mesin Bending 90° dengan Pendekatan Preventive Maintenanceberdasar Metode Keandalan dan FMEA Di PT. Rinnai Indonesia-Cikupa," Jurnal Taguchi: Jurnal Ilmiah Teknik dan Manajemen Industri, pp. 175-184, 2022.
- [8] A. A. El-Sayed, "n optimization model for preventive maintenance scheduling considering imperfect maintenance actions," *Journal of Quality in Maintenance Engineering*, *25(3)*, pp. 343-358, 2019.
- [9] H. Tarakci, "Two types of learning effects on maintenance activities," *International Journal of Production Research*, pp. 1721-1734, 2016.
- [10] Ahmed, R., Memon, Z. A., Memon, S. A., Memon, S. F., & Qureshi, A. A, "A Comprehensive Review of Corrective Maintenance: Definitions, Methods, and Challenges," *IEEE Access*, 9, pp. 62502-62518, 2021.
- [11] M. J. H. d. B. d. Jonge, "Condition-based maintenance in the cyclic patrolling repairman problem," *International Journal of Production Economics*, vol. 222, pp. 1-20, 2020.
- [12] S. G. R. Dicky Reza, "Analisis Kerusakan Mesin Mandrel Tension Reel Dengan Metode Failure Mode And Effect Analysis (FMEA)," Seminar Nasional Riset Terapan, pp. 190-195, 2017.
- [13] D. Kececioglu, Realiability Engineering Handbook, vol. 2, Pennsylvania U.S.A: Destech Publications, incLancaster, 2002.
- [14] Prabhakar, K., Haranath, G., & Raghavan, N. R. S, Handbook of performability engineering, India: Springer, 2016.
- [15] Jain, P. K., & Jain, P. K, Reliability Engineering and Management, Ltd: PHI Learning Pvt, 2018.
- [16] Stamatis, D. H, Failure mode and effect analysis: FMEA from theory to execution (2nd ed.), Indonesia: ASQ Quality Press, 2013.
- [17] U. K. d. D. P. M. Mohammed Ben-Daya, Introduction To Maintenance Engineering Modeling, Optimization. and Management, United Kingdom: Wiley, 2016.
- [18] ,. I. K. a. P. F. Maciej Kuboń, "Reliability of technical systems and the methodology for calculating MTBF using Flexsim computer simulation," E3S Web of Conferences 132, vol. 132, pp. 1-8, 2019.
- [19] M., I. I. Oki Sunardi, "Analisis Efektivitas Mesin dengan Total Productive Analisis Efektivitas Mesin dengan Total Productive," Jurnal Teslink : Teknik Sipil dan Lingkungan, vol. 4, no. 2, pp. 98-106, 2022.
- [20] M. A. F. d. Nurhalim, "Analisis Reliability Centered Maintenance (Rcm) Pada Mesin Hydraulic Press Plate Machine 1000 Ton (Studi Kasus PT. X)," *J-Proteksion: Jurnal Kajian Ilmiah dan Teknologi Teknik Mesin*, vol. 4, no. 2, pp. 19-23, 2020.
- [21] A. D. J. A. D. J. Ario Kurnianto, "Analisa Penerapan Preventive Maintenance pada Mesin Kompresor Sentrifugal dengan Menggunakan Metode Mean Time Between Failure dan Mean Time to Repair," *Jurnal Kajian Teknik Mesin*, vol. 8, no. 1, pp. 80-86, 2023.
- [22] Y. Sinambela, "Analisis Perawatan Mesin Cetak Offset Heidelberg dengan Metode Total Productive Maintenance," *Jurnal Optimalisasi*, vol. 6, no. 2, pp. 156-164, 2020.
- [23] F. A. d. P. A. Wicaksono, "Lean Maintenance Pada Transmission Case Td Line Untuk Mereduksi Waste Guna Meningkatkan Efektivitas Dan Efisiensi Perawatan Mesin Di PT Mitsubishi Krama Yudha Motors & Manufacturing," *Industrial Engineering Online Journal*, vol. 12, no. 3, 2023.
- [24] H. B. H. d. N. A. Nugraha, "Usulan Pembaharuan jadwal Kegiatan Preventive Maintenance pada Mesin Curing PCR PT.XYZ Menggunakan Metoda Distribusi Weibull," *Jurnal Teknologi dan Rekayasa Manufaktur*, vol. 1, no. 1, pp. 23-35, 2019.
- [25] J. S., A. S., W. A. Hilman Sholih, "Analisis Kerusakan Pneumatic Caterpillar Untuk Meningkatkan Availability Performance Mesin Extruder Tipe 150," *Journal Of Mechanical Engineering Manufactures Materials And Energy*, vol. 6, no. 1, pp. 70-85, 2022.
- [26] K. Ignatius, "Total Productive Maintenance (TPM) pada Proses Produksi Kardus di PT. Multipak Unggul," Jurnal Titra, vol. 10, no. 2, pp. 89-96, 2022.
- [27] S. S. d. T. H. Rima Melati Simanungkalit, "Analisis Penerapan Sistem Perawatan dengan Menggunakan Metode Reliability Centered Maintenance (RCM) pada Cement Mill Type Tube Mill di PT Cemindo Gemilang Medan," *Blend Sains Jurnal Teknik*, vol. 2, no. 1, pp. 72-73, 2023.
- [28] Y. D. R. M. A. A. Murwan Widyantoro, "Optimization Machine Maintenance Model With Consider Repair Costs and Number of Repairman at PT. SNP," *Optimization Machine Maintenance Model With Consider Repair Costs* and Number of Repairman at PT. SNP, vol. 20, no. 1, pp. 438-443, 2022.
- [30] S. A. B. W. d. H. S. Indra Widarmadi, "Analysis of the auto lube system electric grease pump against the unscheduled breakdown of the dump truck unit brand k type HD 1500-7," *Jurnal Terapan Teknik Mesin*, vol. 4, no. 2, pp. 197-206, 2023.

🚽 turnitin

• 8% Overall Similarity

Top sources found in the following databases:

• 8% Submitted Works database

TOP SOURCES

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

Aspen University on Submitted works	2024-01-07	2%
2 Federal University of Submitted works	f Technology on 2023-05-16	1%
3 KTH - The Royal Inst Submitted works	titute of Technology on 2012-10-08	<1%
4 Universitas Bina Dar Submitted works	ma on 2023-03-15	<1%
5 Universitas Darma P Submitted works	Persada on 2023-02-15	<1%
6 Universitas Muhamn Submitted works	nadiyah Ponorogo on 2023-11-23	<1%
7 University of Limeric Submitted works	ck on 2022-11-21	<1%
8 UTC Heathrow on 20 Submitted works	023-05-12	<1%
9 Universidad EAFIT o Submitted works	n 2022-06-28	<1%

turnitin

10	DeVry, Inc. on 2015-05-15 Submitted works	<1%
11	Brunel University on 2024-01-11 Submitted works	<1%
12	Institut Teknologi Kalimantan on 2023-05-29 Submitted works	<1%
13	Cranfield University on 2010-01-22 Submitted works	<1%
14	Universitas Singaperbangsa Karawang on 2023-06-26 Submitted works	<1%
15	Brunel University on 2024-01-11 Submitted works	<1%
16	Kennedy-Western University on 2003-08-07 Submitted works	<1%
17	Open University Malaysia on 2023-04-08 Submitted works	<1%
18	Multimedia University on 2010-09-28 Submitted works	<1%